

Features:



Harumoto(HMT) Unique / Patented
 Supports OD0.50 mm~OD1.80mm Cable
 Insulation/Jacket Material: not FEP
 Temperature resistance : 120°C
 Can not soldering
 High-Frequency Option Available ¹
 RoHS II Compliant ²
 Halogen Free ³

SGS NO : CE/2011/C1524

CE/2011/C1525

測試項目 (Test Items)	單位 (Unit)	測試方法 (Method)	方法偵測 極限值 (MDL)	結果 (Result) No.1
鎘 / Cadmium (Cd)	mg/kg	參考IEC 62321: 2008方法, 以感應耦合電 漿原子發射光譜儀檢測. / With reference to IEC 62321: 2008 and performed by ICP-AES.	2	n.d.
鉛 / Lead (Pb)	mg/kg		2	8
汞 / Mercury (Hg)	mg/kg		2	n.d.
六價鉻 / Hexavalent Chromium Cr(VI)	mg/kg	參考IEC 62321: 2008方法, 以UV-VIS檢測. / With reference to IEC 62321: 2008 and performed by UV-VIS.	2	n.d.

測試項目 (Test Items)	單位 (Unit)	測試方法 (Method)	方法偵測 極限值 (MDL)	結果 (Result) No.1
鹵素 / Halogen				
鹵素 (氟) / Halogen-Fluorine (F) (CAS No.: 14762-94-8)	mg/kg	參考BS EN 14582:2007, 以離子層 析儀分析. / With reference to BS EN 14582:2007. Analysis was performed by IC.	50	n.d.
鹵素 (氯) / Halogen-Chlorine (Cl) (CAS No.: 22537-15-1)			50	n.d.
鹵素 (溴) / Halogen-Bromine (Br) (CAS No.: 10097-32-2)			50	n.d.
鹵素 (碘) / Halogen-Iodine (I) (CAS No.: 14362-44-8)			50	n.d.

- 1.) DC~6GHz, VSWR < 1.5 (Industry Standard)
 DC~15GHz, VSWR < 1.5 (Available for Special Order)
- 2.) Pb : 1000 ppm Max. (Industry Standard)
 Pb : 50 ppm Max. (Available for Special Order)
- 3.) Cl + Br (halogen) 1,500 PPM (Industry Standard)
 F + Cl + Br + I (Halogen Family, 300 PPM Available for Special Order)

SALES OFFICES

Headquarters & Intl'Sales Office

HMT CABLE MANUFACTURING CORPORATION

ADD: 301, Building 88, the Fifth Industrial Zone, Mashantou Community, Ma Tian Street, Guangming District, Shenzhen, China

Tel : +86-755-2771-0581

Cell Phone: +86-138-2335-1983

E-mail: sc_chen@harumoto.com service@harumoto.com salesassistant@harumoto.com

Web Site: www.harumoto.com